

## High Performance Schottky Rectifier 320A/100V

### FEATURES


- 175°C T<sub>J</sub> operation
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead (Pb)-free
- Designed and qualified for industrial level
- International standard package SOT-227
- Low I<sub>RM</sub> values

### DESCRIPTION

The NST320S100C Schottky rectifier module series has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 175 °C junction temperature.

### TYPICAL APPLICATIONS

- High current switching power supplies
- Plating power supplies
- UPS system
- Converters
- Freewheeling diode
- Welder
- Reverse battery protection.



### PRODUCT SUMMARY

I <sub>F(AV)</sub>	320A
V <sub>R</sub>	100V

### MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	VALUES	UNIT
I <sub>F(AV)</sub>	Rectangular waveform	160 x 2	A
V <sub>R(RM)</sub>		100	V
I <sub>F(SM)</sub>	t <sub>p</sub> = 5 μs sine	12000	A
V <sub>F</sub>	160 Apk, T <sub>J</sub> = 125°C	0.80	V
T <sub>J</sub>	Range	-55 to 175	°C

### VOLTAGE RATINGS

PARAMETER	SYMBOL	NST320S100C	UNIT
Maximum DC reverse voltage	V <sub>R</sub>	100	V
Maximum working peak reverse voltage	V <sub>R(WM)</sub>		

ABSOLUTE MAXIMUM RATINGS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNIT
Maximum average forward current per leg	$I_{F(AV)}$	50% duty cycle at $T_C = 100^\circ\text{C}$ , rectangular waveform		160	A
Maximum peak one cycle non-repetitive surge current	$I_{FSM}$	5 $\mu\text{s}$ sine or 3 $\mu\text{s}$ rect. pulse	Following any rated load condition and with rated $V_{RRM}$ applied	12000	
		10 ms sine or 6 ms rect. pulse		1400	
Non-repetitive avalanche energy	$E_{AS}$	$T_J = 25^\circ\text{C}$ , $I_{AS} = 15\text{A}$ , $L = 100\mu\text{H}$		11.3	mJ
Repetitive avalanche current	$I_{AR}$	Current decaying linearly to zero in 1 $\mu\text{s}$ $f = 10\text{KHz}$ , $V_A = 1.5 \times V_R$ typical		1.5	A


ELECTRICAL SPECIFICATIONS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNIT
Maximum forward voltage drop per leg	$V_{FM}^{(1)}$	160A	$T_J = 25^\circ\text{C}$	0.98	V
		320A		1.21	
		160A	$T_J = 125^\circ\text{C}$	0.80	
		320A		1.05	
Maximum reverse leakage current per leg	$I_{RM}^{(1)}$	$T_J = 25^\circ\text{C}$	$V_R = \text{Rated } V_R$	2	mA
		$T_J = 125^\circ\text{C}$		30	
Maximum junction capacitance per leg	$C_T$	$V_R = 5 V_{DC}$ (test signal range 100 kHz to 1 MHz) $25^\circ\text{C}$		2500	pF
Typical series inductance per leg	$L_S$	From top of terminal hole to mounting plane		6.0	nH
Maximum voltage rate of change	$dV/dt$	Rated $V_R$		10000	V/ $\mu\text{s}$

**Note**

(1) Pulse width < 500  $\mu\text{s}$ , duty cycle < 2%


THERMAL-MECHANICAL SPECIFICATIONS					
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Maximum junction and storage temperature range	$T_J, T_{Stg}$	-55	-	175	$^\circ\text{C}$
Thermal resistance, junction to case	$R_{thJC}$	-	-	0.30	$^\circ\text{C/W}$
Thermal resistance, case to heatsink	$R_{thCS}$	-	0.15	-	
Weight		-	30 (1.06)	-	g(oz.)
Mounting torque, $\pm 10\%$	to heatsink, M4	-	1.1 (9.7)	-	N·m (lbf·in)
	busbar, M4	-	1.1 (9.7)	-	
Case style		JEDEC SOT-227 module (Non-insulated)			

## Ordering Information Tabel




- 1 - Nell's high power module
- 2 - Package indicator, "ST" for SOT-227
- 3 - Maximum average forward current, 320 = 160A x 2
- 4 - S = Schottky family
- 5 - Voltage rating (100 = 100V)
- 6 - Circuit configuration, Center tap common cathode, non-insulated


**Fig.1 Maximum forward voltage drop characteristics**




**Fig.2 Typical values of reverse current vs. reverse voltage**




**Fig.3 Maximum thermal impedance  $R_{th(j-c)}$  characteristics**




**Fig.4 Typical junction capacitance vs. reverse voltage**




**Fig.5 Maximum allowable case temperature vs. Average forward current**



**Fig.6 Forward power loss characteristics**




**Fig.7 Unclamped Inductive test circuit**



**Note**

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig.6)  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1-D)$ ;  $I_R$  at  $V_{R1}$  = rated  $V_R$

## SOT-227



All dimensions in millimeters (inches)

### Notes

- Dimensioning and tolerancing per ANSI Y14.5M-1982
- Controlling dimension: millimeter